

# HD-575



## FM-MPX 8-Track 4 Channel "Matrix" Stereo Radio and Tape Player

With the HD-575 HAMMOND brings together in one player all the features most desired by the sophisticated buyer: Quality, style, power, size, versatility; they are all here in one package. The acutely sensitive FM-MPX tuner — the 8-track playback deck coupled to the powerful amplifier and leaves nothing to be desired, except "Matrix". Press the "Matrix" switch and the HAMMOND 4 channel "Matrix" circuit surrounds you with sound as it was meant to be heard. Full! Rich! Real! To all of this add individual volume and tone slide controls for left and right side, burglar alarm, program reading lamp, and you have it all. Styled in beautiful walnut grain finish and soft brushed gold.

**HAMMOND**  
**SOUND PRODUCTS**

A DIVISION OF CALIFORNIA AUTO RADIO, INC.

WEST COAST OFFICE: 9300 Hall Rd., Downey, Calif. 90241 (213) 869-4041

MIDWEST OFFICE: 16750 S. Vincennes Rd., South Holland, Illinois 60473

EAST COAST OFFICE: 225 W. Commercial Ave., Moonachie, N.J. 07074 (201) 935-2144

## MODEL NO. HD-575

### PRODUCT DESCRIPTION

FM-MPX 8-TRACK CAR STEREO WITH "MATRIX" 4 CHANNEL SOUND

#### FEATURES:

Sleek shark design  
Slide volume controls—Left and Right channel  
Slide tone controls—Left and Right channel  
"Matrix"—4 channel "Matrix" system "splits" 2 channel stereo music into 4 distinct parts for full dimensional sound.  
Ultra sensitive FM-MPX stereo radio  
FM stereo indicator light  
Smoked glass radio dial  
Digital track lights  
Pushbutton track selector  
Tape program reading light  
Built-in burglar alarm  
Walnut grain and brushed gold finish

### TECHNICAL SPECIFICATIONS

**Unit**.....HD-575  
**Type**.....8-track playback / "Matrix" 4 channel / FM-MPX tuner  
**Frequency Range** .....88-108 MHz  
**IF** .....10.7 MHz  
**Max. Sensitivity** .....Less than 10  $\mu$ V  
**FM MPX Separation**.....More than 20 dB  
**Max. Output Power**.....12 watts per channel  
**Frequency Response** .....70-10,000 Hz  
**Output Impedance**.....4 or 8 ohm  
**Signal to Noise Ratio** .....More than 40 dB  
**Cross Talk**.....More than 40 dB  
**Power Supply**.....DC 13.2V (11V—16V)  
**Polarity**.....Negative Ground  
**Tape Speed** .....3 $\frac{3}{4}$  i.p.s.  
**Wow & Flutter**.....Less than 0.3%  
**Weight** .....5.5 lbs.  
**Dimension** .....2 $\frac{3}{8}$ "H x 7 $\frac{1}{4}$ "W x 7"D

